

# Control Box **DKC3**

DKC3 is designed for electrical lifting desk, table and height adjustable work station, which is able to perform smooth synchronized or single motor movement. It also supports real-time height display and position memory function.




#### **Feature**


- Main applications: Furniture
- Input voltage: 100 ~ 240V AC, 50/60Hz (SMPS)
- Output voltage: 24V DC / 32V DC
- Max. current: 4.5A for 24V or 6A for 32V, per channel
- Power supply: Internal SMPS, 24V/4A or 32V/4A
- Max. number of motors / actuators: 2 channels (synchronization)
- Max. number of controls: 1 channel
- Real-time height display
- Position memory function
- Soft start / stop function
- Anti-pinch function (draw back automatically while detecting resistance)
- Duty cycle: 10%, max. 2 min. continuous operation in 20 min.
- IP Protection level: IP20
- Protection class: Class II
- Color: Black
- Power cord length: 3000 mm
- Certified: CE Marking, EMC Directive 2014/30/EU and LVD Directive 2014/35/EU

# Compatibility


Product	Model	Compatible requirement
Motor / Actuator	DLC2 Lifting column DKL3 Desk lifting column DKM4-LF Gear motor FD60-24-A4 Actuator	With dual Hall effect sensors With Moteck L1-type minifit 6-pin plug
Control	DKP3	Moteck S2 control category With Moteck E-type RJ 10-pin plug
	DKP4	Moteck P2 control category Max. 2 buttons With Moteck E-type RJ 10-pin plug


## **Dimensions**






#### Socket






Actuator socket for L1-type minifit 6-pin, 180° plug







### **Ordering Key**





- 1. Please contact sales for software parameters adjustment according to required function and characteristics of actuator/legs used.
- 2. Refer to data sheets of compatible controls for operating guide.

