



Tuleje montażowe

Tuleje TAPER LOCK



Tuleja 1008 średnica (D1) = 35 szerokość (L) = 22,3 typ śruby: 1/4" x 1,2" moment dokręcania = 5,6 Nm				
kod	d (ISO E8)	B	T2	[kg]

T0655	10	4	1,80	0,16
T0427	11	4	1,80	0,13
T0428	12	4	1,80	0,12
T0429	14	5	2,30	0,12
T0430	15	5	2,30	0,11
T0431	16	5	2,30	0,11
T0432	18	6	2,80	0,10
T0433	19	6	2,80	0,10
T0434	20	6	2,80	0,09
T0435	22	6	2,80	0,08
T0436	24	8	1,30	0,07
T0437	25	8	1,30	0,07

Tuleja 1210 średnica (D1) = 47,5 szerokość (L) = 25,4 typ śruby: 3/8" x 5/8" moment dokręcania = 20 Nm				
kod	d (ISO E8)	B	T2	[kg]

T0450	11	4	1,80	0,28
T0451	12	4	1,80	0,28
T0452	14	5	2,30	0,27
T0453	15	5	2,30	0,26
T0454	16	5	2,30	0,26
T0455	18	6	2,80	0,25
T0456	19	6	2,80	0,24
T0457	20	6	2,80	0,24
T0458	22	6	2,80	0,22
T0459	24	8	3,30	0,21
T0460	25	8	3,30	0,21
T0461	28	8	3,30	0,18
T0462	30	8	3,30	0,17
T0463	32	10	3,30	0,15

Tuleja 1108 średnica (D1) = 38 szerokość (L) = 22,3 typ śruby: 1/4" x 1,2" moment dokręcania = 5,6 Nm				
kod	d (ISO E8)	B	T2	[kg]

T0656	10	4	1,80	0,16
T0438	11	4	1,80	0,16
T0439	12	4	1,80	0,15
T0440	14	5	2,30	0,15
T0441	15	5	2,30	0,14
T0442	16	5	2,30	0,14
T0443	18	6	2,80	0,13
T0444	19	6	2,80	0,13
T0445	20	6	2,80	0,12
T0446	22	6	2,80	0,11
T0447	24	8	3,30	0,10
T0448	25	8	3,30	0,09
T0449	28	8	1,30	0,07

Tuleja 1215 średnica (D1) = 47,5 szerokość (L) = 38,1 typ śruby: 3/8" x 5/8" moment dokręcania = 20 Nm				
kod	d (ISO E8)	B	T2	[kg]

T0464	14	5	2,30	0,38
T0465	16	5	2,30	0,37
T0466	18	6	2,80	0,35
T0467	19	6	2,80	0,34
T0468	20	6	2,80	0,34
T0469	22	6	2,80	0,32
T0470	24	8	3,30	0,29
T0471	25	8	3,30	0,29
T0472	28	8	3,30	0,26
T0473	30	8	3,30	0,23
T0474	32	10	3,30	0,20