



Tuleje montażowe

Tuleje TAPER LOCK



Tuleja 1610				
średnica (D1) = 57 szerokość (L) = 25,4 typ śruby: 3,8" x 5,8" moment dokręcania = 20 Nm				

kod	d (ISO E8)	A	T2	[kg]
T0475	12	4	1,80	0,41
T0476	14	5	2,30	0,41
T0477	15	5	2,30	0,40
T0478	16	5	2,30	0,40
T0479	18	6	2,80	0,39
T0480	19	6	2,80	0,38
T0481	20	6	2,80	0,38
T0482	22	6	2,80	0,37
T0483	24	8	3,30	0,36
T0484	25	8	3,30	0,35
T0485	28	8	3,30	0,32
T0486	30	8	3,30	0,30
T0487	32	10	3,30	0,29
T0488	35	10	3,30	0,26
T0489	38	10	3,30	0,23
T0490	40	12	3,30	0,21
T0491	42	12	1,80	0,19

Tuleja 1615				
średnica (D1) = 57 szerokość (L) = 38,1 typ śruby: 3,8" x 5,8" moment dokręcania = 20 Nm				

kod	d (ISO E8)	A	T2	[kg]
T0492	14	5	2,30	0,58
T0493	16	5	2,30	0,58
T0494	18	6	2,80	0,56
T0495	19	6	2,80	0,55
T0496	20	6	2,80	0,55
T0497	22	6	2,80	0,53
T0498	24	8	3,30	0,50
T0499	25	8	3,30	0,49
T0500	28	8	3,30	0,47
T0501	30	8	3,30	0,45
T0502	32	10	3,30	0,41
T0503	35	10	3,30	0,38
T0504	38	10	3,30	0,32
T0505	40	12	3,30	0,29
T0506	42	12	1,80	0,26

Tuleja 2012				
średnica (D1) = 70 szerokość (L) = 31,8 typ śruby: 7/16" x 7/8" moment dokręcania = 31 Nm				

kod	d (ISO E8)	A	T2	[kg]
T0507	15	5	2,30	0,78
T0508	16	5	2,30	0,78
T0509	18	6	2,80	0,76
T0510	19	6	2,80	0,76
T0511	20	6	2,80	0,75
T0512	22	6	2,80	0,74
T0513	24	8	3,30	0,72
T0514	25	8	3,30	0,71
T0515	28	8	3,30	0,68
T0516	30	8	3,30	0,66
T0517	32	10	3,30	0,64
T0518	35	10	3,30	0,60
T0519	38	10	3,30	0,57
T0520	40	12	3,30	0,54
T0521	42	12	3,30	0,51
T0522	45	14	3,80	0,46
T0523	48	14	3,80	0,40
T0524	50	14	3,80	0,37

Tuleja 2517				
średnica (D1) = 85,5 szerokość (L) = 44,5 typ śruby: 1,2" x 1" moment dokręcania = 48 Nm				

kod	d (ISO E8)	A	T2	[kg]
T0525	19	6	2,80	1,62
T0526	20	6	2,80	1,60
T0527	22	6	2,80	1,57
T0528	24	8	3,30	1,57
T0529	25	8	3,30	1,56
T0530	28	8	3,30	1,52
T0531	30	8	3,30	1,49
T0532	32	10	3,30	1,45
T0533	35	10	3,30	1,40
T0534	38	10	3,30	1,40
T0535	40	12	3,30	1,35
T0536	42	12	3,30	1,27
T0537	45	14	3,80	1,20
T0538	48	14	3,80	1,13
T0539	50	14	3,80	1,08
T0540	55	16	4,30	0,96
T0541	60	18	4,40	0,81
T0542	65	18	4,40	0,65