



TULEJE TAPER LOCK



Tuleja 4040

średnica (D1) = 146
szerokość (L) = 101,8
typ śruby: 5/8" x 1" 3/4
moment dokręcania = 170 Nm

kod	d (ISO E8)	B	T2	[kg]
T0601	45	14	3,80	9,86
T0602	48	14	3,80	9,66
T0603	50	14	3,80	9,48
T0604	55	16	4,30	9,27
T0605	60	18	4,40	8,93
T0606	65	18	4,40	8,65
T0607	70	20	4,90	8,17
T0608	75	20	4,90	7,78
T0609	80	22	5,40	7,35
T0610	85	22	5,40	6,89
T0611	90	25	5,40	6,36
T0612	95	25	5,40	5,94
T0613	100	28	6,40	5,27

Tuleja 4545

średnica (D1) = 162
szerokość (L) = 114,3
typ śruby: 3/4" x 2"
moment dokręcania = 192 Nm

kod	d (ISO E8)	B	T2	[kg]
T0614	55	16	4,30	13,15
T0615	60	18	4,40	12,76
T0616	65	18	4,40	12,38
T0617	70	20	4,90	12,02
T0618	75	20	4,90	11,57
T0619	80	22	5,40	11,05
T0620	85	22	5,40	10,46
T0621	90	25	5,40	9,99
T0622	95	25	5,40	9,42
T0623	100	28	6,40	8,63
T0624	110	28	6,40	7,37

Tuleja 5050

średnica (D1) = 178
szerokość (L) = 127
typ śruby: 7/8" x 2" 1/4
moment dokręcania = 271 Nm

kod	d (ISO E8)	B	T2	[kg]
T0625	70	20	4,90	16,70
T0626	75	20	4,90	16,05
T0627	80	22	5,40	15,56
T0628	85	22	5,40	15,00
T0629	90	25	5,40	14,43
T0630	95	25	5,40	13,88
T0631	100	28	6,40	13,05
T0632	110	28	6,40	11,56
T0633	120	32	7,40	9,78
T0634	125	32	7,40	9,05