




Koła pod pasy klinowe

Koła pod pasy klinowe pod tuleję TAPER LOCK

SPC/8



Materiał: żeliwo EN-GJL-200 UNI EN1561

kod	typ	ilość rowków	P	O	rodzaj wykonania	tuleja TAPER LOCK	otwór mac	E	F	J	K	L	M	N
K0734	SPC 200/8	8	200	209,6	3	3535	90	-	213	144	62	89	62	-
K0735	SPC 212/8	8	212	221,6	3	3535	90	-	213	156	62	89	62	-
K0736	SPC 224/8	8	224	233,6	3	3535	90	-	213	168	62	89	62	-
K0737	SPC 236/8	8	236	245,6	3	3535	90	-	213	180	62	89	62	-
K0738	SPC 250/8	8	250	259,6	3	3535	90	-	213	194	62	89	62	-
K0739	SPC 265/8	8	265	274,6	3	3535	90	-	213	209	62	89	62	-
K0740	SPC 280/8	8	280	289,6	3	3535	90	-	213	224	62	89	62	-
K0741	SPC 300/8	8	300	309,6	3	4040	100	-	213	244	55,5	102	55,5	-
K0742	SPC 315/8	8	315	324,6	3	4040	100	-	213	259	55,5	102	55,5	-
K0743	SPC 335/8	8	335	344,6	6	4040	100	50	213	279	55,5	102	55,5	210
K0744	SPC 355/8	8	355	364,6	6	4040	100	40	213	299	55,5	102	55,5	210
K0745	SPC 375/8	8	375	384,6	6	4545	110	30	213	319	49,5	114	49,5	242
K0746	SPC 400/8	8	400	409,6	6	4545	110	30	213	344	49,5	114	49,5	242
K0747	SPC 425/8	8	425	434,6	6	4545	110	30	213	369	49,5	114	49,5	240
K0748	SPC 450/8	8	450	459,6	6	5050	125	30	213	394	43	127	43	267
K0749	SPC 475/8	8	475	484,6	6	5050	125	30	213	419	43	127	43	267
K0750	SPC 500/8	8	500	509,6	6	5050	125	30	213	444	43	127	43	267
K0751	SPC 530/8	8	530	539,6	6	5050	125	30	213	474	43	127	43	267
K0752	SPC 560/8	8	560	569,6	5	5050	125	-	213	504	43	127	43	267
K0753	SPC 630/8	8	630	639,6	5	5050	125	-	213	574	43	127	43	267
K0754	SPC 710/8	8	710	719,6	5	5050	125	-	213	654	43	127	43	267
K0755	SPC 800/8	8	800	809,6	5	5050	125	-	213	737	43	127	43	267
K0756	SPC 1000/8	8	1000	1009,6	5	5050	125	-	213	937	43	127	43	267
K0757	SPC 1250/8	8	1250	1259,6	5	5050	125	-	213	1187	43	127	43	267