



Tuleje montażowe

Tuleje TAPER LOCK



Tuleja 4040 średnica (D1) = 146 szerokość (L) = 101,8 typ śruby: 5,8" x 1" 3/4 moment dokręcania = 170 Nm					Tuleja 4545 średnica (D1) = 162 szerokość (L) = 115 typ śruby: 3,4" x 2" moment dokręcania = 192 Nm				
kod	d (ISO E8)	B	T2	[kg]	kod	d (ISO E8)	B	T2	[kg]
T0601	45	14	3,80	9,86	T0614	55	16	4,30	13,15
T0602	48	14	3,80	9,66	T0615	60	18	4,40	12,76
T0603	50	14	3,80	9,48	T0616	65	18	4,40	12,38
T0604	55	16	4,30	9,27	T0617	70	20	4,90	12,02
T0605	60	18	4,40	8,93	T0618	75	20	4,90	11,57
T0606	65	18	4,40	8,65	T0619	80	22	5,40	11,05
T0607	70	20	4,90	8,17	T0620	85	22	5,40	10,46
T0608	75	20	4,90	7,78	T0621	90	25	5,40	9,99
T0609	80	22	5,40	7,35	T0622	95	25	5,40	9,42
T0610	85	22	5,40	6,89	T0623	100	28	6,40	8,63
T0611	90	25	5,40	6,36	T0624	110	28	6,40	7,37
T0612	95	25	5,40	5,94					
T0613	100	28	6,40	5,27					

Tuleja 5050 średnica (D1) = 178 szerokość (L) = 127 typ śruby: 7/8" x 2" 1/4 moment dokręcania = 271 Nm				
kod	d (ISO E8)	B	T2	[kg]
T0625	70	20	4,90	16,70
T0626	75	20	4,90	16,05
T0627	80	22	5,40	15,56
T0628	85	22	5,40	15,00
T0629	90	25	5,40	14,43
T0630	95	25	5,40	13,88
T0631	100	28	6,40	13,05
T0632	110	28	6,40	11,56
T0633	120	32	7,40	9,78
T0634	125	32	7,40	9,05

*Na zapytanie tuleje 4030 oraz 5040.