





# Koła pod pasy klinowe

Koła pod pasy klinowe pod tuleję TAPER LOCK

SPA/2



Materiał: żeliwo EN-GJL-200 UNI EN1561

kod	typ	ilość rowków	P	O	rodzaj wykonania	tuleja TAPER LOCK	otwór mac	E	F	J	K	L	M	N
K0216	SPA 63/2	2	63	68,5	8	1008	28	-	35	32,5	13	22	-	-
K0217	SPA 67/2	2	67	72,5	8	1108	28	-	35	37	13	22	-	-
K0218	SPA 71/2	2	71	76,5	8	1108	28	-	35	40	13	22	-	-
K0219	SPA 75/2	2	75	80,5	8	1108	28	-	35	44	13	22	-	-
K0220	SPA 80/2	2	80	85,5	8	1210	32	-	35	50	10	25	-	-
K0221	SPA 85/2	2	85	90,5	8	1210	32	-	35	55	10	25	-	-
K0222	SPA 90/2	2	90	95,5	8	1610	42	-	35	59	10	25	-	-
K0223	SPA 95/2	2	95	100,5	8	1610	42	-	35	63	10	25	-	-
K0224	SPA 100/2	2	100	105,5	8	1610	42	-	35	66	10	25	-	-
K0225	SPA 106/2	2	106	111,5	8	1610	42	-	35	72	10	25	-	-
K0226	SPA 112/2	2	112	117,5	8	1610	42	-	35	78	10	25	-	-
K0227	SPA 118/2	2	118	123,5	8	1610	42	-	35	84	10	25	-	-
K0228	SPA 125/2	2	125	130,5	8	1610	42	-	35	91	10	25	-	-
K0229	SPA 132/2	2	132	137,5	8	2012	50	-	35	98	3	32	-	-
K0230	SPA 140/2	2	140	145,5	8	2012	50	-	35	106	3	32	-	-
K0231	SPA 150/2	2	150	155,5	8	2012	50	-	35	116	3	32	-	-
K0232	SPA 160/2	2	160	165,5	8	2012	50	-	35	125	3	32	-	-
K0233	SPA 170/2	2	170	175,5	8	2012	50	-	35	135	3	32	-	-
K0234	SPA 180/2	2	180	185,5	6	2012	50	10	35	146	1,5	32	1,5	108
K0235	SPA 190/2	2	190	195,5	6	2012	50	10	35	156	1,5	32	1,5	108
K0236	SPA 200/2	2	200	205,5	7	2517	60	10	35	165	5	45	5	123
K0237	SPA 212/2	2	212	217,5	7	2517	60	18	35	177	5	45	5	123
K0238	SPA 224/2	2	224	229,5	7	2517	60	18	35	189	-	45	10	124
K0239	SPA 236/2	2	236	241,5	7	2517	60	12	35	202	-	45	10	124
K0240	SPA 250/2	2	250	255,5	7	2517	60	12	35	215	5	45	5	124
K0241	SPA 280/2	2	280	285,5	7	2517	60	12	35	245	-	45	10	124
K0242	SPA 300/2	2	300	305,5	7	2517	60	12	35	265	-	45	10	124
K0243	SPA 315/2	2	315	320,5	7	2517	60	12	35	280	-	45	10	124
K0244	SPA 355/2	2	355	360,5	4	2517	60	-	35	320	-	45	10	124
K0245	SPA 400/2	2	400	405,5	4	2517	60	-	35	365	-	45	10	124
K0246	SPA 450/2	2	450	455,5	4	2517	60	-	35	465	-	45	10	124
K0247	SPA 500/2	2	500	505,5	4	2517	60	-	35	525	-	45	10	125
K0248	SPA 630/2	2	630	635,5	4	3020	75	-	35	595	8	51	18	159