Controlled document
Pivexin Technology Sp. z o.o.

MS17HD6P4050







Wiring Diagram



Exciting Sequence vs. Direction of Rotation

STEP	A	B	C	D
1	+	+	−	−
2	−	+	+	−
3	−	−	+	+
4	+	−	−	+

CW ↓ (step 1 → 4) ; CCW ↑ (step 4 → 1)

Clockwise view from mounting side

Hybrid Stepping Motor Specifications		
1.	Number of Phase	2
2.	Step Angle	1.8°
3.	Rated Voltage	12 V DC
4.	Rated Current	0.5 Amp
5.	Holding Torque	0.67 Nm Typ. (Two phase on/rated current) ①
6.	Phase Resistance	24 ohm±10% (20℃)
7.	Phase Inductance	53 mH±20%(1kHz 1V rms) ①
8.	Rotor Interia	82 gcm^2
9.	Motor Weight	0.36 kg
10.	Insulation Class	B (130℃)

C-C(3:1)



④③②① Label Detail (2:1)

XXXXXXXX-Work order
XXXX-Serial number



REV.	REVISION RECORD	DATE
C2	ECR:24-1127;There are 2 positions ④	2024.07.11
C1	ECR:23-317 ③	2023.03.29
C0	Update nameplate ②	2017.04.24
B0	620mNm,52mH,change the nameplate ①	2013.01.24
A0	Original revision	2011.07.18

Unit:mm

First angle method

Tolerances for linear and angular dimensions without individual tolerance indications GB/T 1804-m eqv ISO 2768-1:m

Geometrical tolerance for features without individual tolerance indications GB/T 1184-K eqv ISO 2768-2:K

UNLESS OTHERWISE SPECIFIED

NAMES	SIGNATURE	DATE
Approve		
Standardize		
Process Review		
Check		
Design		

PIVEXIN TECHNOLOGY

Drawing No: 4611110008902 | Rev. C2 | SCALE: 1:1 | Sheet 1 of 1